

TH-C1420-P / TH-C1417-PO

ACTIVELY COOLED 20W CW LINEAR BAR ARRAY (17W CW COLLIMATED)

DESCRIPTION

The TH-C1420-P product is a highly performing 20W CW Laser Diode Bar Array soldered on a water cooled package. The Laser Diode structure is multiple emitters spaced on a monolithic 1cm "bar". The bar is mounted P side down, with the active region towards an actively cooled submount.

The epitaxial quantum well structure and the process quality, lead to high electrical/optical conversion efficiency and reliability. The actively cooled package has a specific design for efficient thermal management. Fast axis collimation is also proposed, TH-C1417-PO, with the adjonction of a compact optics. This product is an unique solution for flexible integrations to implement powerful solid state laser pumping, illuminators...



TH-C1417-PO (collimated)

MAIN FEATURES

- 20 W CW optical power
- A collimated beam version
- Actively cooled package
- Monolithic linear array
- 795 to 860nm wavelength range
- Highly reproducible MOCVD process
- Highly reliable product

SPECIFICATIONS

Fluid temperature : 25°C

Flow rate : 1 l/mn

PARAMETERS	TH-C1420-P	TH-C1417-PO collimated	UNITS
CW output power	20	17	Watt
Emitting area	10 x 0.001	10 x 0.6	mm x mm
Threshold current	7	7	Amp.
Operating current	27	29	Amp.
Operating voltage	1.85	1.85	Volt
Total efficiency	42	33	%
Beam divergence (FWHM)	10 x 35	10 x 1	degree

Note :

- Variation of wavelength is approximately 0.26 to 0.3 nm/°C
- Standard wavelength is 808nm
- Tolerance on wavelength is +/- 3nm
- Spectral width is \leq 3nm FWHM
- Other wavelength selections are available in the range of 795nm to 860nm

ABSOLUTE MAXIMUM RATINGS

PARAMETERS	TH-C1420-P	TH-C1417-PO	UNITS
CW output power	24	20	Watt
Reverse voltage	3	3	Volt
Operating temperature	+5 to +35	+5 to +35	°C
Storage temperature	-40 to +85	-40 to +85	°C

Note : Operation at temperature below dew point requests to use dry N2 environment

PACKAGE SPECIFICATION :

- dimensions are in mm
- standard tolerances are ± 0.2 mm

COOLING

- : Water
- Flow : 1 l/mn
- Pressure : 0.5 bar
- Temperature : 25 °C

For further information please contact:

THALES LASER DIODES - Route Départementale 128 - BP 46 - 91401 ORSAY Cedex / France

Tel : (33) 1 69 33 06 61

Fax : (33) 1 69 33 06 62

E-mail : infotld@fr.thalesgroup.com

<http://www.laser-diodes.thomson-csf.com>

Information furnished is believed to be accurate and reliable. However THALES LASER DIODES assumes no responsibility for the consequences of use of such information nor for any infringement or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of THALES LASER DIODES. Specifications mentioned in this publication are subjected to change without notice. This publication supersedes and replaces all informations previously supplied. THALES LASER DIODES products are not authorized for use as critical components in life support devices or systems without express written approval from THALES LASER DIODES. © 2001 THALES LASER DIODES Printed in France All rights reserved.